

SPECIFICATION

TITLE OF THE INVENTION

LIQUID COOLING SYSTEM AND PERSONAL COMPUTER USING THEREOF

BACKGROUND OF THE INVENTION

5 The present invention relates to a liquid cooling system for cooling body generating heat therefrom, and in particular, to such a liquid cooling system being suitable for the structure of being small and/or thin in sizes thereof.

10 Semiconductor devices, being used in electronic apparatuses, such as a computer, etc., generate heat thereby when it operates. In particular, high-integrated semiconductor devices in recent years increase an amount of the heat generating thereby. Since the semiconductor device loses the function thereof if temperature thereof exceeds a certain value, cooling is necessary for such
15 the semiconductor device having a large amount of heat generation therewith.

20 For a method for cooling the semiconductor device of an electronic apparatus, there are known various manners, such as of adopting thermal conduction or air-cooling, or using a heat pipe, or by means of liquid cooling.

Cooling of adopting the thermal conduction can be achieved by applying materials having large thermal conductivity on a route

of heat radiating, reaching from the semiconductor device to an outside of the electronic apparatus. This method is suitable for so-called a compact electronic apparatus, in which heat generation is relatively small, such as a notebook-type personal computer.

5 With the cooling by using air, an air blower or fan is provided inside the electronic apparatus, thereby achieving the cooling of the semiconductor device therein through compulsively circulating air thereon. This method is adopted widely for cooling of the semiconductor device having a certain amount of heat
10 generation, and it was also applied to the personal computer by making the air blower small and thin in the sizes thereof.

Cooling with using the heat pipe, in which heat is carried out to an outside of the electronic apparatus by means of coolant enclosed within a pipe, was described in Japanese Patent
15 Laying-Open No. Hei 1-184699 (1989), and Japanese Patent Laying-Open No. Hei 2-244748 (1989), for example. With this method, since there is provided no part of consuming electric power therein, such as the air blower or fan, therefore it has good efficiency, i.e., increases the cooling of the thermal conduction further.
20 However, with this method, there is a limit in an amount of heat that can be transferred therewith.

The cooling by means of liquid coolant is suitable for the cooling of the semiconductor device having a large amount of heat generation, and it was described, for example, in Japanese Patent
25 Laying-Open No. Hei 5-1335454 (1993), Japanese Patent Laying-Open No. Hei 6-97338 (1994), Japanese Patent Laying-Open No. Hei 6-125188 (1994), and Japanese Patent Laying-Open No. Hei 10-213370 (1998), for example. However, such the cooling system of liquid is restricted in the field of utilization thereof, such as a
30 large-scale computer. This is, because the cooling system of liquid necessitates a large number of parts, such as a pump, pipe system, heat radiation fin, etc., being exclusive use for the cooling, the apparatus comes to be large in sizes, and it is difficult to

maintain reliability of using the liquid for cooling comparing to other methods. It is also one of reasons, the fact that no such the semiconductor device requiring such the cooling by means of liquid is used other than a field of the large-scale computer.

5 A technology of adopting the liquid cooling into a small-sized apparatus, including such the notebook-sized personal computer, is described in Japanese Patent Laying-Open No. Hei 6-266474 (1994). In this prior art, a header attached onto the semiconductor device and a heat radiation pipe separately located from it are connected
10 with each other by means of a flexible tube, wherein heat is transferred through the liquid flowing therein, thereby obtaining the cooling thereof.

However, an amount increases up remarkably of heat generation from the semiconductor devices, which are used in the electronic
15 devices, such as a personal computer, a sever computer, a work station, etc., in recent years, then only adoption of such the conventional art is not sufficient for applying it into the electronic apparatuses, being required to be small and thin in sizes much more, in particular, such as the notebook-type personal
20 computer.

SUMMARY OF THE INVENTION

An object of the present invention, therefore, is to provide a liquid cooling system being able to cool down high heat generated by a heat generating body, such as, the semiconductor device or
25 element, which is used in such the electronic apparatus of being small and thin in sizes thereof, and also to provide a personal computer equipped with such the structure therein.

Such the object as mentioned above, according to the present invention, is accomplished by the construction of a liquid cooling
30 system of superior efficiency, being small and thin in sizes, or a personal computer equipped with such the liquid cooling system,

being peculiar to such the personal computer, which is small and thin in the sizes thereof.

A pump is necessary for promotion of circulation of liquid in the liquid cooling system, however with a pump of rotational type, which is usually applied to, it is impossible to realize, in particular, in viewpoints of such ultra-small and thin sizing, and the low electric power consumption, as well. For this reason, it is effective to apply a pump of pressurizing the liquid through reciprocal movement of a member. However, even when using such the pump of reciprocal type, it is necessary to satisfy the following conditions, for the purpose of constructing a system of low electric power consumption, enabling cooling effectively.

In more details, according to the present invention, there is provided a liquid cooling system, comprising: a pump for supplying cooling liquid in a form of pulsation; a heat receiving jacket being supplied with said cooling liquid, and for receiving heat generated from a heat generating body; a heat radiation pipe for radiating heat which is supplied by the cooling liquid passing through said heat receiving jacket; and a passage for circulating the cooling liquid passing through said heat radiation pipe into said pump, wherein said cooling liquid circulates within a closed flow passage, and further ΔV_s is equal to or greater than ΔV_p , assuming that inner volume change when said pump emits the pulsation therefrom is the ΔV_p , that pressure caused accompanying with said volume change is P , and that volume change due to said pressure P in the flow passage of the cooling liquid ΔV_p other than portion of said pump.

Further, for an example, said pump emits the pulsation by the reciprocal movement of the member within the pump, and the reciprocal movement of the member of said pump is caused by bending or flexure of the diaphragm. This diaphragm itself or a driving source of the diaphragm is preferably formed with a piezo element,

from viewpoints of small-sizing, low electric power consumption and low noises, etc. With this, it is possible to maintain a carrying amount of the cooling liquid, even in the computer being small and thin in sizes, thereby to obtain effective cooling.

5 Also, a rubber pipe or a resin pipe may be used in at least a portion of the connector pipe, constructing the flow passage for carrying said cooling liquid therein, and further the surface of said resin or rubber pipe is coated with a metal film or a resin sheet covered with a metal film, thereby suppressing diffusion
10 of the cooling liquid through the rubber and the resin into the atmosphere, and enabling conduction of heat with efficiency, as well.

The liquid cooling system defined in the above, preferably, further comprises an accumulator, in which the volume change of
15 the cooling liquid owned by itself due to said pressure P is equal or greater than the ΔV_p , from a viewpoint of management of pressure.

Further, the accumulator has such the structure that it retains the cooling liquid therein and is able to change the retaining amount thereof. For example, it may be a such one that
20 it changes the retaining amount by deformation of itself. Or alternatively, it may be in such the structure that it keeps gas further within an inside thereof.

The accumulator mentioned above may be made of contractual material, such as rubber or resin, for example, thereby being
25 movable due to the change in the pressure. Or, it may be constructed by utilizing the construction of metal bellows. Or, it may adopt a piston mechanism thereto.

Further, in the liquid cooling system of the above, it is preferable that said cooling liquid is pressurized at pressure
30 being equal to or higher than that of an atmosphere.

Also, in the liquid cooling system of the above, said accumulator comprises a supply opening for supplying said circulating cooling liquid therethrough and a discharge opening for discharging said cooling liquid therethrough, and it maintains
5 gas and said cooling liquid therein. It is preferable for said accumulator to be disposed in series with the heat receiving jacket or/and the heat radiation pipe.

Further, as a personal computer having such the liquid cooling system, according to the present invention, there is provided a
10 personal computer, comprising: a semiconductor element; a signal input portion; a display device; and a liquid cooling system, including: a pump for supplying cooling liquid in a form of pulsation; a heat receiving jacket being supplied with said cooling liquid, and for receiving heat generated within said semiconductor
15 element; a heat radiation pipe for radiating heat which is supplied by the cooling liquid passing through said heat receiving jacket; and a passage for circulating the cooling liquid passing through said heat radiation pipe into said pump, wherein said cooling liquid circulates within a closed flow passage, and further ΔV_s is equal
20 to or greater than ΔV_p , assuming that inner volume change when said pump emits the pulsation therefrom is the ΔV_p , that pressure caused accompanying with said volume change is P , and that volume change due to said pressure P in the flow passage of the cooling liquid ΔV_p other than portion of said pump.

25 Furthermore, as a notebook-type personal computer, there is provided a personal computer, comprising: a main body including a semiconductor element and a signal input portion; a display device having a display portion, being connected with said main body through a movable mechanism; and a liquid cooling system,
30 including: a pump for supplying cooling liquid in a form of pulsation; a heat receiving jacket being disposed within said main body and supplied with said cooling liquid, and for receiving heat generated within said semiconductor element; a heat radiation pipe

being disposed in a back surface of said display portion of said display device, and for radiating heat which is supplied by the cooling liquid passing through said heat receiving jacket; and a passage for circulating the cooling liquid passing through said heat radiation pipe into said pump, wherein said cooling liquid circulates within a closed flow passage, and said display device comprises an accumulator comprising: a supply opening for supplying said circulating cooling liquid therethrough; and a discharge opening for discharging said cooling liquid therethrough, and maintains gas and said cooling liquid therein, wherein, an amount of the cooling liquid maintained within said accumulator is changed responding to emission of the pulsation from said pump.

Moreover, as a detailed embodiment according to the present invention, there is provided a personal computer, comprising: a semiconductor element; a signal input portion; a display device; and a liquid cooling system, including: an emission pump for supplying cooling liquid in a form of pulsation by using reciprocating movement of a diaphragm having a piezo element; a heat receiving jacket being supplied with said cooling liquid, and for receiving heat generated within said semiconductor element; a heat radiation pipe for radiating heat which is supplied by the cooling liquid passing through said heat receiving jacket; an accumulator comprising, a supply opening for supplying said circulating cooling liquid therethrough and a discharge opening for discharging said cooling liquid therethrough, and for maintaining gas and said cooling liquid therein; and a passage for circulating the cooling liquid passing through said heat radiation pipe into said pump, wherein said cooling liquid circulates within a closed flow passage, and said display device comprises wherein, said cooling liquid circulates within a closed flow passage, and, an amount of the cooling liquid maintained within said accumulator is changed responding to emission of the pulsation from said pump.

Next, explanation will be given by referring to Fig. 13.

The flow passage in the liquid cooling system according to the present invention will be shown in the Fig. 13. The flow passage is constructed with a pump 1 and connector pipes 3, and cooling liquid is filled up within an inside thereof. The connector pipe 3 is connected to both an outlet and an inlet of the pump, thereby forming a closed loop. The pump 1 is constructed with a diaphragm 8 performing reciprocal movement and check valves 9a and 9b, and a case. Now, considering a case where the diaphragm comes to the position of a solid line, since the cooling liquid within the pump is pressurized, then the check valve 9b is opened. Repeating this operation, continually, the pulsation is emitted from the pump, thereby to circulate the cooling liquid within the route thereof. In this instance, for the cooling liquid to move in the direction of arrows, it is necessary that a portion or the entire connector pipe 3 be expanded, so that the cooling liquid within the pump flows into that direction.

Fig. 14 shows a relationship between flow rate Q of the pump and the pressure P . Herein, P_{\max} indicates the maximum pressure that is generated or developed when the exit of the pump is closed so that no cooling liquid flows therethrough, and Q_{\max} the maximum flow rate when the exit of the pump is opened, so as to remove the pressure loss away therefrom. In this graph, the relationship between the flow rate Q and the pressure P can be determined, and then the flow rate comes to be Q_0 when a pipe of pressure loss P_0 is connected, for example.

In the liquid cooling system according to the present invention, since the cooling liquid is circulated within the flow passage with the pulsation thereof, by applying such the reciprocating pump therein, the volume change ΔV_p due to supply of the pulsation (i.e., due to the reciprocating movement) can be obtained from $Q/(\text{number of vibration } f)$, therefore the relationship between the volume change ΔV_p and the pressure P can be drawn as shown in Fig. 15. Also, since the pressure P applied

on the pipe and the volume change ΔV_s are proportional to each other, the relationship comes to be indicated by a straight line (1), for example. In this instance, at a point where the straight line (1) and the characteristic curve of the pump come across, pressure P_1 and volume change ΔV_1 can be determined. In a case of forming an open loop, the volume change is determined by the pressure loss P_0 of the pipe, thereby obtaining the volume change ΔV_0 , however if using a rigid or hard pipe having small volume change therein, as indicated by (1), only the volume change of ΔV_1 can be obtained, being smaller than the ΔV_0 . Accordingly, the flow rate comes down, and then the cooling performance also comes down. On the contrary to this, in a case where the volume change with respect to the pressure is large, as is indicated by (1), namely, in the case of using a soft pipe, since the volume change ΔV_0 come to be large at the crossing point of the straight line (2) with the characteristic curve of the pump, the primary volume change can be obtained at the ΔV_0 , therefore it is possible to show up sufficient characteristics. Thus, if defining that the volume change due to the reciprocal movement of the pump member is ΔV_p , pressure caused when occurring the volume change ΔV_p is P , volume change of the expansible portion 10 when the pressure P is applied thereon is ΔV_s , it is possible to draw out the characteristics of the liquid cooling system at high efficiency, by making ΔV_s larger than ΔV_p , therefore it is possible to construct the system of low electric power consumption therein.

Also, in a liquid cooling system comprising two (2) pumps for pressurizing the liquid by means of the reciprocal movement of members, the heat receiving jacket having function of heat exchanger for cooling the heat generating body, the heat radiation pipe for conducting heat exchange with an outside air, and the connector pipe for connecting those parts mentioned above, wherein the two (2) pumps, the heat receiving jacket and the heat radiation pipe are disposed in a closed loop by means of the connector pipe,

and the cooling liquid is filled up within the two (2) pumps, the heat receiving jacket, the heat radiation pipe, and the connector pipe, therefore the same effect can be obtained with shifting by 180 degree, in the phase of reciprocal movements of the members
5 of the pumps provided in the number of two (2), therefore it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, thereby to construct a system of low electric power consumption.

BRIEF DESCRIPTION OF THE DRAWINGS

10 Those and other features, objects and advantages of the present invention will become more apparent from the following description when taken in conjunction with the accompanying drawings wherein:

15 Fig. 1 shows a perspective view of a notebook-type personal computer utilizing the liquid cooling system, according to an embodiment of the present invention;

Fig. 2 shows a view of the liquid cooling system, according to an embodiment of the present invention;

20 Fig. 3 shows a view of the liquid cooling system, according to other embodiment of the present invention;

Fig. 4 shows a view of other liquid cooling system, according to an embodiment of the present invention;

Fig. 5 shows a view of the liquid cooling system, according to further other embodiment of the present invention;

25 Fig. 6 shows a view of other liquid cooling system, according to the further embodiment of the present invention;

Fig. 7 shows a view of the liquid cooling system, according

to further other embodiment of the present invention;

Fig. 8 shows a view of the liquid cooling system, according to further other embodiment of the present invention;

Fig. 9 shows a view of the liquid cooling system, according to further other embodiment of the present invention;

Fig. 10 shows a cross-sectional view of a connection pipe used in any embodiment of the present invention;

Fig. 11 also shows a cross-sectional view of a connection pipe used in any embodiment of the present invention;

Fig. 12 shows a view of the liquid cooling system, according to further other embodiment of the present invention;

Fig. 13 shows a principle of the liquid cooling system for explanation about basic law of the present invention;

Fig. 14 shows a graph for showing a relationship between flow rate and pressure of a pump which is used in the liquid cooling system, according to the embodiment of the present invention; and

Fig. 15 shows a graph for showing a relationship between volume change and pressure of the pump which is used in the liquid cooling system, according to the embodiment of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

Hereinafter, embodiments according to the present invention will be fully explained by referring to the attached drawings.

Fig. 1 shows a notebook-type personal computer using the liquid cooling system according to the present invention. To a

semiconductor element or device 5 installed within a main body chassis or housing 6 is connected a heat receiving jacket 2, in which a flow passage is provided. In the a main body chassis 6 is also provided a pump 1. Behind a display panel of a display device chassis 7 is provided a heat radiation pipe 4. The pump 1, the heat receiving jacket 2, the heat radiation pipe 4 are connected with a connector pipe 3 in a closed loop-like manner, as shown in the figure, and in an inside of them is filled up with a cooling liquid.

Fig. 2 shows a first embodiment of the cooling system of the notebook-type personal computer shown in the Fig. 1, diagrammatically. The pump 1, the heat receiving jacket which is connected onto the semiconductor element 5 mounted on a print board 11, and the heat radiation pipe 4 are connected with, by means of the connector pipes 3. The pump 1 is constructed with a diaphragm conducting reciprocal movement therein and check valves 9a and 9b, as well as a case. A portion of the connector pipe 3 is made of a soft material, so as to form an expansible portion 10 therewith. When the diaphragm 8 comes to the position shown in the figure, the cooling liquid is suppressed, and then the check valve 9b is opened. Then, due to the pressure of the cooling liquid, the expansible portion 10 is expanded, therefore the cooling liquid moves in a direction of an arrow. Next, when the diaphragm comes back to the position of broken line, since the pressure falls down, the check valve 9a is opened, and the cooling liquid within the connector pipe flows into an inside of the pump while the expansible portion 10 turns back to the original position indicated by broken line. Repeating of this operation makes the cooling liquid circulating in the flow passage. The cooling liquid warmed up in the heat receiving jacket 2 is cooled down in the heat radiation pipe 4, and it flows into the heat receiving jacket again via the pump 1. Repeating this makes possible effective cooling, even of the semiconductor element having a large amount of heat generation therefrom. (In particular, it is effective when it is applied into a personal computer having a semiconductor element, which emits

heat generation over 30W.)

According to the present embodiment, if defining that the volume change due to the reciprocal movement of the pump member is ΔV_p , pressure caused when occurring the volume change ΔV_p is P , volume change of the expansible portion 10 when the pressure P is applied thereon is ΔV_s , then ΔV_s is larger than ΔV_p . Because of this, as was mentioned in the "Summary of the Invention", it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, thereby to construct a system of low electric power consumption.

Measurement of values of those mentioned above can be performed by the following manner, for example.

The connector pipe 3 for collecting the cooling liquid into the pump 1 is cut off just in front thereof. A pressure gauge is provided just below the pump 1 in downstream side of the pump 1. The cooling liquid is supplied from a source of cooling liquid to the pump 1, and then the pump 1 is driven. And then, the flow rate and the pressure " P_0 " are measured. Next, an amount of the volume change (ΔV_p) mentioned above is obtained as the flow rate per one (1) revolution, from the frequency of pulsation (i.e., the reciprocal movement of an inner member) of the pump 1.

Next, the connector pipe, being cut off, is hermetically sealed at an end of the side opposing to the pump 1, and the personal computer and so on are positioned so that the flow passage of the cooling liquid comes to be in as horizontal as possible. And then, a column of water is connected to the connector pipe, which is cut off, at the side of the pump, so as to measure the volume change ΔV_s and the pressure P_1 in the flow passages of cooling water other than the pump, through change in height of the water column and/or height thereof. On a P-V graph, V_s and P_1 are plotted, and a straight line is drawn from the origin. In case of comparing the straight

line with the plotted points of P_0 and ΔV_p , the P_0 has a larger value when comparing the both pressures on the ΔV_p .

Further, the connector pipe 3 is made softer in a portion thereof in the present embodiment, thereby to obtaining a function of bringing the ΔV s to be equal or greater than ΔV_p , however it may be softer as a whole, so as to achieve the function of bringing the ΔV s to be equal or greater than ΔV_p . Also, such a material can be listed, as a material of the connector, for example, rubber of low rigidity or resin.

Fig. 3 shows the liquid cooling system according to a second embodiment of the present invention, diagrammatically. The structure of the system is almost equal to that of the first embodiment, however in the place of the expansible portion 10 in the first embodiment, an accumulator 12 is attached, which is filled up with the cooling liquid therein. In this figure, also solid lines and broken lines of the diaphragm 8 correspond to those of the accumulator 12. When the pump 1 is compressed within an inside thereof by means of the diaphragm 8, the check valve 9b is opened, and then the pressure is transferred to the accumulator 12, therefore it is expanded as shown by the solid lines. Due to this expansion, the cooling liquid can flow in the direction of arrows. In the present embodiment, the volume change of the accumulator 12 is ΔV_s , which is caused when the pressure P is applied thereon, and the ΔV s is equal or greater than the ΔV_p . Therefore, it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, thereby to construct a system of low electric power consumption.

In the present embodiment, though the accumulator 12 is attached to the connector pipe 3 branching off therefrom, however the accumulator 13 may be connected to the connector pipe 3 in series, as shown in Fig. 4, so as to insert it into a closed loop, thereby obtaining the same effect, as far as the ΔV s is equal or

greater than the Δv_p .

Also, in a case where the accumulator 12 or 13 has the structure of changeable, i.e., becomes large or small in sizes, as a material of the accumulator 12 or 13, rubber of low rigidity or resin can be listed up, for example. On a while, in the place thereof, such the structure also can be considered that a gas portion (for example, air, etc.) and a delay portion for the cooling liquid are provided within an inside of the accumulator. The accumulator 12 or 13 may be provided with a supply opening for supplying the cooling liquid therethrough, and an exit opening (not shown in the figure) for discharging the cooling liquid standing in the accumulator 12 or 13.

Further, though the accumulator is disposed on the route between the pump 1 and the heat receiving jacket 2 in the present embodiment, however, more preferably from a viewpoint of effective small-sizing thereof, etc., within the display device chassis 7 in the Fig. 1, as well as, on the route between the pump 1 and the heat receiving jacket 2. More preferably, it may be positioned in a downstream side of a region where the heat radiation pipe 4 is disposed, from a viewpoint of protection from corrosion, etc.

Fig. 5 shows the liquid cooling system according to a third embodiment of the present invention, diagrammatically. The structure of the system is almost equal to that of the second embodiment shown in the Fig. 3, however a metal bellows 14 is attached to as the accumulator. Also in this figure, solid lines and broken lines of the diaphragm 8 correspond to those of the metal bellows 14. When the pump 1 is compressed within an inside thereof by means of the diaphragm 8, the check valve 9b is opened, and then the pressure is transferred to the metal bellows 14, therefore it is expanded as shown by the solid lines. With this expansion, the cooling liquid can flow in the direction of arrows. In the present embodiment, the volume change of the metal bellows 14 is ΔV_b , being

caused when the pressure P is applied thereupon, and the ΔV_s is equal or greater than the ΔV_p . Therefore, it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, thereby to construct a system of low electric power consumption.

Furthermore, in the present embodiment, though the metal bellows 14 is attached to the connector pipe 3 branching off therefrom, however the metal bellows 14 may be connected to the connector pipe 3 in series, as shown in Fig. 6, so as to insert it into a closed loop, thereby obtaining the same effect, as far as the ΔV_s is equal or greater than the ΔV_p . And, for example, stainless steel and phosphor bronze can be listed up, as the material of the metal bellows 14.

Fig. 7 shows the liquid cooling system according to a fifth embodiment of the present invention, diagrammatically. The structure of the system is almost equal to that of the second or third embodiment, however a piston mechanism 16 is applied as the accumulator. The piston mechanism 16 has such the structure as an injector or syringe, and it is pushed up at one end thereof by means of a spring. When the pump 1 is compressed within an inside thereof by means of the diaphragm 8, the check valve 9b is opened, and then the pressure is transferred to the piston mechanism 16, therefore the piston is shifted upward in the Fig. 7. With this shifting, the cooling liquid can flow in the direction of arrows. In the present embodiment, the volume change of the piston mechanism 16 is ΔV_s , being caused when the pressure P is applied thereupon, and the ΔV_s is equal or greater than the ΔV_p through adjusting strength of the spring adequately. Therefore, it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, thereby to construct a system of low electric power consumption. As the material of the piston mechanism 16, metal, resin and glass can be listed up, however it is also possible to use the injector or syringe available on the market.

As the spring used in the piston mechanism 16, there can be listed up, for example, a plate spring, an air spring, etc., other than the coil spring shown in the Fig. 7.

Fig. 8 shows the liquid cooling system according to a fifth embodiment of the present invention, diagrammatically. The structure of the system is almost equal to that of the second embodiment, however the cooling liquid is filled up with pressure. In this figure, also solid lines and broken lines of the diaphragm 8 correspond to those of an accumulator 17. Also, an original shape (a shape of no difference in pressure between outside and inside thereof) of the accumulator 17 is shown by one-chained dotted lines. Since the cooling liquid is filled up with pressure, the shape of the accumulator 17 is larger than the original one even when the diaphragm 8 of the pump 1 comes to the position shown by broken lines. Even if the cooling liquid is pressurized to be filled up, it is possible to obtain the same effect to that of the first embodiment, if the volume change ΔV_s of the accumulator 17, being caused when the pressure P is applied thereupon, is equal or greater than the ΔV_p , therefore it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, thereby to construct a system of low electric power consumption.

As a distinctive effect according to the present embodiment, it is possible to point out that the cooling liquid can be protected from bubbles generated from a long-time use thereof in the system. Using of rubber or resin, as the material of the connector 3 or the accumulator 17, causes diffusion of molecular of the cooling liquid therein, though being a very small amount, thereby it sneaks away into an atmosphere. If the pressure within the system is lower than the atmospheric pressure, the air diffuses into the rubber or resin, to sneak into the flow passage, therefore, there is a possibility of generating the bubbles therein. The bubbles may disturb or obstruct the operation of the check valve, therefore,

it is important for the present system to prevent from them.

Further, it is needless to say that the effect, being completely same to that of the present embodiment, can be obtained by filling up the cooling liquid with pressure, even in the first, the third and the forth embodiments.

Fig. 9 shows the liquid cooling system according to a sixth embodiment of the present invention, diagrammatically. The structure of the system is almost equal to that of the first embodiment, however soft rubber or resin is used as the material of the connector pipe 3, in the present embodiment. And, surface of the connector pipe 3 is covered or coated with metal film 18 around it, as shown in Fig. 10. As the distinctive effect of the present embodiment can be listed up that, since the connector pipe 3 is made of the soft material, other parts, such as the pump, the heat receiving jacket, the heat radiation pipe, etc., can be positioned freely. Also, it is possible to fold a portion of the heat radiation route repetitively. However, if using the rubber or resin, the molecular of cooling liquid diffuses therein, as was explained in the fifth embodiment, therefore it may sneak away into the atmosphere. According to the present embodiment, since the surface of the connector pipe 3 is covered with the metal film 18, it is possible to prevent the cooling liquid from reduction thereof. Also, as shown in Fig. 11, the same effect can be obtained by covering the connector pipe with a resin sheet 19, including a metal films 19a and a resin film 19b. In this case, it does not matter if there is defined space between the resin sheet 19 and the connector pipe 3, however they must be closely adhered to each other at both ends thereof.

Fig. 12 shows the liquid cooling system according to a seventh embodiment of the present invention, diagrammatically. In the present embodiment, two (2) pumps are provided in series, thereby forming a flow passage of closed loop. Solid lines and broken lines of the diaphragms 8 and 8' correspond to each other. When the

diaphragm 9 of the pump 1 lies at the position of the solid line, so as to pressurize the cooling liquid therewith, the diaphragm 8' of the pump 1' lies in the position of the solid line, therefore the cooling liquid emitted from the pump 1 flows into the pump 1'. In this manner, since the two (2) of the pumps are shifted by 180 degree in the phase of reciprocal movements of the diaphragms thereof, the cooling liquid can flow in the direction of arrows, therefore obtaining the effects being totally same to those of the other embodiments, i.e., it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, thereby to construct a system of low electric power consumption.

Furthermore, in the present embodiment, there is no need of providing such an expansible portion in the flow passage, like the other embodiments, however it does not matter to apply it in common with that of the other embodiments.

However, since two (2) of the pumps are used in the present embodiment, the pressure of compression comes to be large, thereby increasing the flow rate, therefore it has a distinctive effect that the cooling effect can be improved more than those of the other embodiments.

As was mentioned in the above, according to the present embodiment, since it is possible to draw out the characteristics or performances of the liquid cooling system with high efficiency, therefore it is possible to provide the liquid cooling system of ultra-small and thin in sizes, as well as of low electric power consumption, and further it enable to install such the semiconductor element of generating high temperature therefrom into the personal computer, by applying the present system therein.

According to the present invention, as was fully explained in the above, it is possible to provide a liquid cooling system with low electric power consumption, being able to cool down a

body generating high heat therefrom, such as the semiconductor element used in the electronic apparatus being small-sized and thin, or to provide a personal computer equipped with such the structure.

- 5 While we have shown and described several embodiments in accordance with our invention, it should be understood that the disclosed embodiments are susceptible of changes and modifications without departing from the scope of the invention. Therefore, we do not intend to be bound by the details shown and described herein
- 10 but intend to cover all such changes and modifications falling within the ambit of the appended claims.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2